

RKA 185 - 1 POLIG



087810-0-3

ANSCHLUSSQUERSCHNITTE

2 x 185 mm² - 95 mm² (350 kcmil - 3/0 AWG)
150 mm² - 70 mm²



MESSANSCHLUSS

1 x 10 mm² - 1,5 mm² (8 - 16 AWG)
6 mm² - 1,5 mm² (10 - 16 AWG)



- > Modularer Aufbau
- > Beliebig anreihbar
- > Montage auf DIN Schiene TS 35 oder Montageplatte



AL / CU



087810-1-3



087810-2-3



087810-3-3



087810-4-3

Für Aluminium und Kupferleiter (Al/Cu)



NENNSPANNUNG

1000 V AC/DC
600 V

STROMBELASTBARKEIT

353 A Cu
310 A Cu / 250 A Al

ZULASSUNG

IEC 60947-7-1
UL-1059 / CSA C22.2 No.158-10

Ausführung	Artikel Nr.	Typ	VPE	GTIN / EAN
RKA 185 für Aluminium/ Kupferleiter	087810-0-3	RKA 185 L G	1/12	4051589878104
	087810-1-3	RKA 185 N	1/12	4051589878111
	087810-2-3	RKA 185 PE	1/12	4051589878128
	087810-3-3	RKA 185 L B	1/12	4051589878135
	087810-4-3	RKA 185 L S	1/12	4051589878142
	Zubehör			
	087800-0-0	Staubdeckel für RKA 185 Serie	12/216	4051589878005



087800-0-0

Abmessungen:

