

## RKA 300 - 1 POLIG



087910-0-3

### ANSCHLUSSQUERSCHNITTE

2 x 300 mm<sup>2</sup> - 150 mm<sup>2</sup> (600 - 300 kcmil)  
240 mm<sup>2</sup> - 120 mm<sup>2</sup>



### MESSANSCHLUSS

1 x 10 mm<sup>2</sup> - 1,5 mm<sup>2</sup> (8 - 16 AWG)  
6 mm<sup>2</sup> - 1,5 mm<sup>2</sup> (10 - 16 AWG)



- > Modularer Aufbau
- > Beliebig anreihbar
- > Montage auf DIN Schiene TS 35 oder Montageplatte



**AL / CU**



087910-1-3



087910-2-3



087910-3-3



087910-4-3

## Für Aluminium und Kupferleiter (Al/Cu)



### NENNSPANNUNG

1000 V AC/DC  
600 V

### STROMBELASTBARKEIT

520 A Cu  
420 A Cu / 340 A Al

### ZULASSUNG

IEC 60947-7-1  
UL-1059 / CSA C22.2 No.158-10

Ausführung	Artikel Nr.	Typ	VPE	GTIN / EAN
RKA 300 für Aluminium/ Kupferleiter	087910-0-3	RKA 300 L G	1/12	4051589879101
	087910-1-3	RKA 300 N	1/12	4051589879118
	087910-2-3	RKA 300 PE	1/12	4051589879125
	087910-3-3	RKA 300 L B	1/12	4051589879132
	087910-4-3	RKA 300 L S	1/12	4051589879149
	<b>Zubehör</b>			
	087900-0-0	Staubdeckel für RKA 300 Serie	8/144	4051589879002



087900-0-0

Abmessungen:

