

## RKA 300 - 1 POLE



087910-0-3

### TERMINAL CROSS SECTION

2 x 300 mm<sup>2</sup> - 150 mm<sup>2</sup> (600 - 300 kcmil)  
240 mm<sup>2</sup> - 120 mm<sup>2</sup>



### MEASUREMENT CONNECTION

1 x 10 mm<sup>2</sup> - 1,5 mm<sup>2</sup> (8 - 16 AWG)  
6 mm<sup>2</sup> - 1,5 mm<sup>2</sup> (10 - 16 AWG)



- > modular system
- > user-defined stackable
- > to fit on DIN rail TS 35 or installation plate



**AL / CU**



087910-1-3



087910-2-3



087910-3-3



087910-4-3

## For aluminium and copper conductors (Al/Cu)



### NOMINAL VOLTAGE

1000 V AC/DC  
600 V

### NOMINAL CURRENT

520 A Cu  
420 A Cu / 340 A Al

### STANDARDS

IEC 60947-7-1  
UL-1059 / CSA C22.2 No.158-10

Model	Part No.	Type	PU	GTIN / EAN
RKA 300 for aluminium/ copper conductors	087910-0-3	RKA 300 L G	1/12	4051589879101
	087910-1-3	RKA 300 N	1/12	4051589879118
	087910-2-3	RKA 300 PE	1/12	4051589879125
	087910-3-3	RKA 300 L B	1/12	4051589879132
	087910-4-3	RKA 300 L S	1/12	4051589879149
	<b>Accessories</b>			
	087900-0-0	dust cover for RKA 300 series	8/144	4051589879002



087900-0-0

### Dimensions:

