

RKA 95 1/4 - 1 POLIG



087520-0-3

ANSCHLUSSQUERSCHNITTE

4 x 95 mm² - 16 mm² (3/0 - 6 AWG)
70 mm² - 10 mm²



MESSANSCHLUSS

2 x 10 mm² - 1,5 mm² (8 - 16 AWG)
6 mm² - 1,5 mm² (10 - 16 AWG)




- > Modularer Aufbau
- > Beliebig anreihbar
- > Montage auf DIN Schiene TS 35 oder Montageplatte




AL / CU




087520-1-3



087520-2-3



087520-3-3



087520-4-3

Für Aluminium und Kupferleiter (Al/Cu)



NENNSPANNUNG

1000 V AC/DC
1000 V AC/DC
600 V

STROMBELASTBARKEIT

232 A Cu
200 A Al
200 A Cu / 155 A Al

ZULASSUNG

IEC 60947-7-1
EN 61238-1
UL-1059 / CSA C22.2 No.158-10

Ausführung	Artikel Nr.	Typ	VPE	GTIN / EAN
RKA 95 1/4 für Aluminium/ Kupferleiter	087520-0-3	RKA 95 1/4 L G	1/18	4051589875202
	087520-1-3	RKA 95 1/4 N	1/18	4051589875219
	087520-2-3	RKA 95 1/4 PE	1/18	4051589875226
	087520-3-3	RKA 95 1/4 L B	1/18	4051589875233
	087520-4-3	RKA 95 1/4 L S	1/18	4051589875240
	Zubehör	087500-0-0	Staubdeckel für RKA 95 Serie	20/360



087500-0-0

Abmessungen:

