

## RKA 95 1/6 - 1 POLIG



087560-0-3

### ANSCHLUSSQUERSCHNITTE

6 x 95 mm<sup>2</sup> - 16 mm<sup>2</sup> (3/0 - 6 AWG)  
70 mm<sup>2</sup> - 10 mm<sup>2</sup>



- > Modularer Aufbau
- > Beliebig anreihbar
- > Montage auf DIN Schiene TS 35 oder Montageplatte

### MESSANSCHLUSS

3 x 10 mm<sup>2</sup> - 1,5 mm<sup>2</sup> (8 - 16 AWG)  
6 mm<sup>2</sup> - 1,5 mm<sup>2</sup> (10 - 16 AWG)



**AL / CU**



087560-1-3



087560-2-3



087560-3-3



087560-4-3

## Für Aluminium und Kupferleiter (Al/Cu)



### NENNSPANNUNG

1000 V AC/DC  
1000 V AC/DC  
600 V

### STROMBELASTBARKEIT

232 A Cu  
200 A Al  
200 A Cu / 155 A Al

### ZULASSUNG

IEC 60947-7-1  
EN 61238-1  
UL-1059 / CSA C22.2 No.158-10



Ausführung	Artikel Nr.	Typ	VPE	GTIN / EAN
RKA 95 1/6 für Aluminium/ Kupferleiter	087560-0-3	RKA 95 1/6 L G	1/12	4051589875608
	087560-1-3	RKA 95 1/6 N	1/12	4051589875615
	087560-2-3	RKA 95 1/6 PE	1/12	4051589875622
	087560-3-3	RKA 95 1/6 L B	1/12	4051589875639
	087560-4-3	RKA 95 1/6 L S	1/12	4051589875646
	Zubehör	087500-0-0	Staubdeckel für RKA 95 Serie	20/360



087500-0-0

Abmessungen:

