

RKA 95 - 1 POLIG



087510-0-3

ANSCHLUSSQUERSCHNITTE

2 x 95 mm² - 16 mm² (3/0 - 6 AWG)
70 mm² - 10 mm²



MESSANSCHLUSS

1 x 10 mm² - 1,5 mm² (8 - 16 AWG)
6 mm² - 1,5 mm² (10 - 16 AWG)



- > Modularer Aufbau
- > Beliebig anreihbar
- > Montage auf DIN Schiene TS 35 oder Montageplatte



AL / CU



087510-1-3



087510-2-3



087510-3-3



087510-4-3

Für Aluminium und Kupferleiter (Al/Cu)



NENNSPANNUNG

1000 V AC/DC
1000 V AC/DC
600 V

STROMBELASTBARKEIT

232 A Cu
200 A Al
200 A Cu / 155 A Al

ZULASSUNG

IEC 60947-7-1
EN 61238-1
UL-1059 / CSA C22.2 No.158-10

Ausführung	Artikel Nr.	Typ	VPE	GTIN / EAN
RKA 95 für Aluminium/ Kupferleiter	087510-0-3	RKA 95 L G	2/36	4051589875103
	087510-1-3	RKA 95 N	2/36	4051589875110
	087510-2-3	RKA 95 PE	2/36	4051589875127
	087510-3-3	RKA 95 L B	2/36	4051589875134
	087510-4-3	RKA 95 L S	2/36	4051589875141
	Zubehör			
	087500-0-0	Staubdeckel für RKA 95 Serie	20/360	4051589875004



087500-0-0

Abmessungen:

