

## UVB 200 - 1 pole



080030-0-X

### INCOMING

1 x 70 - 10 mm<sup>2</sup>  
50 - 6 mm<sup>2</sup>



- > modular system
- > user-defined stackable
- > to fit on DIN rail TS 35

### OUTGOING/BRIDGE

1 x 35 - 4 mm<sup>2</sup>  
25 - 2,5 mm<sup>2</sup>



### OUTGOING

6 x 16 - 1,5 mm<sup>2</sup>  
10 - 1,5 mm<sup>2</sup>



**AL / CU**



080030-1-X



080030-2-X



080030-3-X



080030-4-X

## For aluminium and copper conductors (Al/Cu)



NOMINAL VOLTAGE	NOMINAL CURRENT	STANDARDS
1000 V AC / 1500 V DC	185 A Al	IEC 61238-1 (Class A)
1000 V AC / 1500 V DC	200 A Cu	IEC 60947-7-1

Model	Part no.	Type	PU	GTIN / EAN
UVB 200 for aluminium/ copper conductors	080030-0-3	UVB 200 L G	3/18	4051589003032
	080030-1-3	UVB 200 N	3/18	4051589003131
	080030-2-3	UVB 200 PE	3/18	4051589003230
	080030-3-3	UVB 200 L B	3/18	4051589003339
	080030-4-3	UVB 200 L S	3/18	4051589003438

## For copper conductors (Cu)



NOMINAL VOLTAGE	NOMINAL CURRENT	STANDARDS
1000 V AC / 1500 V DC	200 A	IEC 60947-7-1

Model	Part no.	Type	PU	GTIN / EAN
UVB 200 for copper conductors	080030-0-4	UVB 200 L G	3/18	4051589800303
	080030-1-4	UVB 200 N	3/18	4051589800310
	080030-2-4	UVB 200 PE	3/18	4051589800327
	080030-3-4	UVB 200 L B	3/18	4051589800334
	080030-4-4	UVB 200 L S	3/18	4051589800341

Dimensions:

